LED POSTERS / LED

HB-X2.5

2.5 mm pixel pitch LED poster display with a 640 × 1920 mm active area, GOB protective process and mobile wheeled base.



Generated product illustration. Final appearance and selected configuration require confirmation.

Installation: Floor-standing

PARAMETER	PUBLISHED VALUE / OPTION
Pixel pitch	2.5 mm
Display resolution	256 × 768 px
Display technology	Direct-view LED · SMD 3-in-1
Active display size	640 × 1920 mm
Overall width × height	646 × 2050 mm
Protective process	GOB
Front protection	IP54 front
Brightness	1000 nits
Module access	Magnetic front access
Refresh rate	≥ 3840 Hz
Content publishing	App · USB · Wi-Fi · Ethernet
Playback modes	Synchronous / asynchronous
Multi-unit joining	Supported · controller and layout to confirm
Optional interfaces	HDMI · wireless 4G (configuration dependent)
Viewing angle	160° horizontal / 160° vertical
Weight	43 kg
Mobile base	4 swivel wheels
Supply voltage	110–240 V
Peak power	430 W
Average power	145 W

Specification notes

Product imagery is a reference-based render of the upright display. Folding and optional battery configurations should be confirmed for your selected model. HDMI and 4G are optional in the source brochure.

Confirm before ordering

- Confirm installation suitability, controller configuration and selected options before ordering.
- Confirm packing dimensions, gross weight, protective case, spare parts and model-specific conformity documents.
- Include the destination, quantity and installation conditions in your inquiry.

Warranty and project support

2-year factory warranty. Coverage, start date and service arrangements are documented in your order agreement.

Factory location: Bao'an District, Shenzhen, China. Contact us for the street address and a visit appointment.

Warranty scope and support procedure

Document basis

This sheet compiles the specifications and planning information published on the product page for this edition. Pending or configuration-dependent items remain subject to written confirmation; this is not a test report, certification or final order specification.

Product page: https://kedaled.com/products/hb-x2-5/

Request configuration documents